

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Flip LED Swing Arm

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
BL-1021L Left	3000K 85	8.5W	489	315	BK Black
BL-1021R Right					BZ Bronze
					TT Titanium

Example: **BL-1021L-BK**

DESCRIPTION

A clever LED swing arm reading light that folds in completely to neatly and orderly fit within modern design elements. Integral memory touch dimmer conveniently located for fingertip control.

FEATURES


- Integral universal driver
- Bauhaus-style geometry in a left and right paired design
- Two 12 inch cord covers included
- Fingertip touch dimming on head
- 8 foot cord included for hard-wired and portable installation
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum hardware with polycarbonate diffuser
Power:	8.5W
Input:	100-240 VAC, 50/60Hz
Rated Life:	30000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard.
Finish:	Black, Bronze, Titanium
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed



FINISHES



LINE DRAWING



BL-1021L



BL-1021R