



Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

Landscape accent luminaire. Simple to retrofit existing line voltage systems or coordinate well with a new commercial landscape installation.

## **FEATURES**

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Detachable shroud, 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

### **ORDERING NUMBER**

	Color Temp	Finish
<b>5012</b> Accent 120V	<b>30</b> 3000K	BK Black on Aluminum BZ Bronze on Aluminum BBR Bronze on Brass

5012-30

Example: 5012-30BBR

**SPECIFICATIONS** 

110V - 120VAC

3.5W to 14.5W

**Brightness:** 100 lm to 900 lm **Beam Angle:** 15° to 60°

85

Rated Life: 45,000 hours

Input:

Power:

CRI:

# **ACCENT 120V**

5012



#### Accessories Easy wiring accessory designed for 12V & 120V products Power Stake M6000-STAKE PVC Eliminates the need for a separate Junction box 5010-SNOOT-BK Black on Aluminum 5010-SNOOT-BZ Bronze on Aluminum Accent Snoot Shields lamp and reduces glare 5010-SNOOT-BBR Bronze on Brass 5010-LSHR-BK Black on Aluminum 6" Long Shroud 5010-LSHR-BZ Bronze on Aluminum Reduce glare. Ideal for downlighting application 5010-LSHR-BBR Bronze on Brass 5000-GM-BZ **Gutter Mount** Stainless Steel universal mounting bracket for gutter mounting Stainless Steel Bracket 5000-GM-BK fixture Bronze on Aluminum box with Stainless steel mounting screws. Tree Mount 5000-TCP-BZ Bronze on Aluminum 5000-TCP-BK Black on Aluminum Two ½" NPT threaded holes Junction Box LENS-20-AMB Amber LENS-20-BLU Optics LENS-20-GRN Green LENS-20-FR Frosted Enhances saturation of florals and foliage LENS-20-RED Red LENS-20-SPR Spread 5000-X18-BZ 18 in 5000-X04-BZ 4 in 5000-X18-BK 18 in 5000-X04-BK 4 in 5000-X24-BZ 24 in 5000-X08-BZ 8 in Extends distance between Accent light and Extension Rods 5000-X24-BK 24 in 5000-X08-BK Surface Mount Canopy, Stake, or Tree Mount box 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in Rod L-Coupler 5000-LCO-BZ Bronze