


# TUBE ARCHITECTURAL DS-WD08

# WAC LIGHTING

## LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

### SPECIFICATIONS

<b>Input:</b>	Universal voltage 120V - 277VAC, 50/60Hz
<b>Dimming:</b>	Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1%
<b>Light Source:</b>	High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70
<b>Finish:</b>	Electrostatically powder coated, white, black, bronze and graphite
<b>Standards:</b>	IP65 rated, ETL & cETL wet location listed Title 24 JA8-2016 Compliant
<b>Operating Temp:</b>	-13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Output <sup>1</sup> Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
DS-WD08	8" 46W x 2	S Straight up and down	18°	927S	2700K	90	3080 x 2	15187	67 x 2		BK Black WT White BZ Bronze GH Graphite
				27S	2700K	85	3865 x 2	19064	84 x 2		
				930S	3000K	90	3275 x 2	16156	71 x 2		
				30S	3000K	85	3935 x 2	19387	86 x 2		
				35S	3500K	85	4030 x 2	19872	88 x 2		
				40S	4000K	85	4095 x 2	20195	89 x 2		
		N Straight up and down	25°	927S	2700K	90	3185 x 2	10536	68 x 2		
				27S	2700K	85	4000 x 2	13226	87 x 2		
				930S	3000K	90	3390 x 2	11208	74 x 2		
				30S	3000K	85	4070 x 2	13450	88 x 2		
				35S	3500K	85	4170 x 2	13786	91 x 2		
				40S	4000K	85	4240 x 2	14010	92 x 2		
		F Straight up and down	35°	927S	2700K	90	3015 x 2	5475	66 x 2		
				27S	2700K	85	3785 x 2	7211	82 x 2		
				930S	3000K	90	3210 x 2	6111	70 x 2		
30S	3000K			85	3850 x 2	7334	84 x 2				
35S	3500K			85	3945 x 2	7517	86 x 2				
40S	4000K			85	4010 x 2	7639	87 x 2				
DS-WD0869	8" 34W x 2	F Away from the wall	N/A	927A	2700K	90	3020 x 2	N/A	66 x 2		
				27A	2700K	85	3790 x 2	N/A	82 x 2		
				930A	3000K	90	3210 x 2	N/A	70 x 2		
				30A	3000K	85	3855 x 2	N/A	84 x 2		
				35A	3500K	85	3950 x 2	N/A	86 x 2		
				40A	4000K	85	4015 x 2	N/A	87 x 2		
F Towards the wall	N/A	927B	2700K	90	3020 x 2	N/A	66 x 2				
		27B	2700K	85	3790 x 2	N/A	82 x 2				
		930B	3000K	90	3210 x 2	N/A	70 x 2				
		30B	3000K	85	3855 x 2	N/A	84 x 2				
		35B	3500K	85	3950 x 2	N/A	86 x 2				
		40B	4000K	85	4015 x 2	N/A	87 x 2				
F One side each	N/A	927C	2700K	90	3020 x 2	N/A	66 x 2	One side away from wall, one side towards the wall			
		27C	2700K	85	3790 x 2	N/A	82 x 2				
		930C	3000K	90	3210 x 2	N/A	70 x 2				
		30C	3000K	85	3855 x 2	N/A	84 x 2				
		35C	3500K	85	3950 x 2	N/A	86 x 2				
		40C	4000K	85	4015 x 2	N/A	87 x 2				

**DS-WD08-** \_\_\_\_\_ - \_\_\_\_\_ Example: **DS-WD08-F930A-WT** <sup>1</sup>Reference output shows 46W output. Multiply by 0.8 to determine output for 34W combinations

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760