

Lotos R - Fire

Rated

Adjustable Downlight 5CCT

| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|---------|-------------|---|--------|------|------------------------|
| R4ERA2R | W 50 | 9CS 2700K/3000K/3500K/4000K/500 0K - 90 | 775 | No | FWT White (Fire Rated) |

Example: R4ERA2R-W9CS-FWT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Fire rated to reduce the spread of flames and maintain the integrity of the ceiling.

FEATURES

- Fire Rated ASTM E119 and UL 263 tested and certified for 2 hours
- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Minimum Plenum Space Required: 4 1/2"
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K/5000K

Input: 120-277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-5% ,TRIAC: 100-5%

Rated Life: 50000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, cETL, Title 24 JA8 Compliant, Energy Star 2.0

Wet Location Listed

Construction: Steel with frosted TIR lens



Fixture Type:

Project:

Location:

Catalog Number:

FINISHES:

White (Fire Rated)

LINE DRAWING:

- Ø1%"

