

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED523 24W W Track Luminaire

System Type & Voltage	Model	Color Temp & CRI	Lumens	CBCP	Finish
WTK-120 VAC	LED523	27 2700K - 85	1340	6840	BK Black
WHK-277 VAC		30 3000K - 85	1500	7595	PT Platinum
		35 3500K - 85	1495	7280	WT White
		40 4000K - 85	1600	7650	
		927 2700K - 90	1260	6515	
		930 3000K - 90	1350	6635	

Example: **WHK-LED523-27-BK**

### DESCRIPTION

Museum-quality LED luminaire with adjustable beam angle. Designed for use on W track systems (120V, 277V).

### FEATURES

- Twist to adjust beam angle between 15° - 60°
- 365° horizontal rotation and 180° vertical aiming
- Driver hidden inside W track
- Integral selector to choose between independently controllable track circuits
- Comparable to 20W HID
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum with cap ring.
<b>Power:</b>	24W
<b>Input:</b>	120 VAC, 277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50000 Hours
<b>Finish:</b>	Electrostatically Powder Coated White, Platinum, Black
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Dry Location Listed



### FINISHES



### LINE DRAWING

