
TUBE ARCHITECTURAL DS-WS05

WAC LIGHTING

LED Wall Mounts

Responsible Lighting®





Fixture Type:
Catalog Number:
Project:
Location:

PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight™ iOS App
- · High performance LED wall mounted light
- Solid die cast aluminum construction
- · 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277V, 50/60Hz

Controls: DMX512-A with advanced commissioning via Bluetooth.

Bluetooth v4.0 - Configured with ilumenight[™] iOS App for localized (within 150ft line of sight) groups of 8 luminaires or less. (DMX512-A hardwire recommended for high wireless signal

interference environments).

Dimming: 100%-1% in CCT & Color via DMX or Bluetooth control **Light Source:** High output 2 Step Mac AdamEllipse LEDs, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

Diameter Power Beam			Delivered Lumens @ 3000K	CBCP @ 3000K	Light Direction				or Temp	Finish			
			S N F	15° 25° 33°	745 645 620	6186 1951 1386	s	Straight up or down		CC Color Changing		вк	Black
Single DS-W	S05 5"	31W	_		840	-	В	Away from the wall			WT BZ GH	White Bronze Graphite	
			F					Towards the wall					

DS-WS05-__-CC-___

Example: DS-WS05-FA-CC-GH




TUBE ARCHITECTURAL DS-WD05

WAC LIGHTING

Color Changing LED Wall Mounts

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight[™] iOS App
- · High performance LED wall mounted light
- Solid die cast aluminum construction
- · 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277V, 50/60Hz

Controls: DMX512-A with advanced commissioning via Bluetooth.

Bluetooth v4.0 - Configured with ilumenight[™] iOS App for localized (within 150ft line of sight) groups of 4 luminaires or less. (DMX512-A hardwire recommended for high wireless signal

interference environments).

Dimming: 100%-1% in CCT & Color via DMX or Bluetooth control **Light Source:** High output 2 Step MacAdam Ellipse LEDs, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

Diameter Power B		Beam	Delivered Lumens @ 3000K	CBCP @ 3000K	Light Direction			Color Temp		Finish		
	31W x2	S 15° N 25° F 33°	645 x2	6186 x2 1951 x2 1386 x2	s	Straight up or down	L	- CC Color Chan				
Double DS-WD05 5"			840 x2	-	A	Away from the wall			Color Changing	BK WT	Black White	
Double D3-WD03 3	3 I VV X2	F			В	Towards the wall			Color Changing	BZ GH	Bronze Graphite	
					С	One side each						

DS-WD05-__-CC-__

Example: DS-WD05-FA-CC-GH

