

Surface Mounted

Step Light

Catalog Number:
Project:
Location:

Model & Voltage	Color Temp & CRI	Lumens	Finish
4901 9-15 VAC	2700K 85 3000K 85	100 100	BBR Bronze on Brass BK Black on Aluminum BZ Bronze on Aluminum WT White on Aluminum

Example: 4901-27BBR

FEATURES

- Slim low profile design-surface mount installation, (no junction box)
- Die-cast aluminum or die-cast brass
- Invisible hardware
- 6' lead wire included
- Compatible with WAC Transformer
- Transformer required
- 10 yrs warranty

SPECIFICATIONS

Corrosion resistant aluminum alloy, Solid die-cast brass Construction:

8W Power:

50/60Hz, 9-15 VAC Input: Integrated LED **Light Source:**

3 Step Mac Adam Ellipse

Tempered Glass Lens: 70000 Hours Rated Life:

Enamel Coated: White on Aluminum, Bronze on Finish:

Aluminum, Black on Aluminum, Bronze on Brass

-40°F to 122°F (-40°C to 50°C) **Operating Temp:**

UL, cUL, Wet Location Listed, IP66, ADA Standards:



FINISHES:










White on Aluminum

Bronze on Aluminum

Black on Bronze on Aluminum

Brass

LINE DRAWING:





12V Magnetic Transformer (Outdoor)

Accessory

Model & Product

9075-TRN-SS 75W Magnetic Landscape Lighting Power Supply in Stainless Steel 9150-TRN-SS 150W Magnetic Landscape Lighting Power Supply in Stainless Steel 9300-TRN-SS 300W Magnetic Landscape Lighting Power Supply in Stainless Steel 9600-TRN-SS 600W Magnetic Landscape Lighting Power Supply in Stainless Steel

Fixture Type:

Catalog Number:

Project:

Location:

LxWxH

13.97IN x 5.35IN x 5.63IN 18.9IN x 6.69IN x 6.3IN 18.9IN x 6.69IN x 6.3IN 14.49IN x 10.08IN x 5.94IN

Example: 9075-TRN-SS

DESCRIPTION

WAC Landscape Lighting Magnetic power supplies are 12V AC to support the entire line of 12V Landscape Lighting products, including Accent, Flood, Well, Indicator, Submersible, 12V Tape Light, Step and Wall, Deck and Patio, Path and Area, and Hardscape lighting products. The Stainless Steel housing enhances protection from corrosive and outdoor elements. Mounting extrusion with variating knockout sizes proved for a simple installation. Heavy gauged grounded and water resistant cord included for simple plug-in power feature. Hinged cover includes a loop to safely lock the power supply with an optional lock to secure access from inner contents. Multiple wire taps ranging from 12V-16V on terminal strip, for long runs where voltage drop may occur. Hinged cover includes a loop to safely lock the power supply with an optional lock to secure access from inner contents.

FEATURES

- Outdoor rated stainless steel transformer contains an outdoor rated 3-prong plug for power
- Knock outs for power and photosensor connections
- · 3-prong outlet for timer
- Taps for 12V, 13V, 14V and 15V
- 6' lead input wire, except for the 600W which comes with a 5' lead wire
- UL 1838 Listed
- MLV Dimming capable, dimming dependent upon fixture type
- 5 year warranty

SPECIFICATIONS

Construction: Stainless steel
Input: 120 VAC, 50/60Hz

Finish: Stainless Steel: Stainless Steel

Operating Temp: -40°F to 122°F (-40°C to 50°C)

Standards: UL, cUL, Wet Location Listed, IP65



FINISHES:



Stainless Steel

LINE DRAWING:

