## WALL WASH 12V

5021



### LANDSCAPE LIGHTING

		Fixture Type:
		Catalog Num
		Project:
0		Location:
8	- 4%" 334"	
10 - 50 21 - 50 21 - 50 21 - 50 21 - 50		

kture Type:	
talog Number:	
oject:	

#### **PRODUCT DESCRIPTION**

Landscape Wall Wash luminaire

#### FEATURES

- A uniform wide distribution wall wash from a small form factor
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV Dimmable with remote MLV Dimmer

#### **ORDERING NUMBER**

		Color Temp		Finish	
5021	Wall wash 12V	27 30	2700K 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

#### 5021-\_\_\_\_

#### Example: 5021-30BK

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

#### SPECIFICATIONS

Input:	9 - 15VAC (Transformer is required)
Power:	2W to 16W / 2VA - 23VA
Brightness:	190 lm to 980 lm
Beam Angle:	15° upward (50° by 80°)
CRI:	85
Rated Life:	70,000 hours

# WALL WASH 12V



# WAC

### LANDSCAPE LIGHTING

Accessories					
Addtional Stake	9000-ST9-BZ		Bronze		Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK		Bronze on Aluminun Bronze on Brass Black on Aluminum	1	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Tree Mount Junction Box	5000-ТСР-ВZ 5000-ТСР-ВК		Bronze on Aluminur Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\mathcal{V}$ " NPT threaded holes
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Optics	LENS-2X4-AMB LENS-2X4-GRN LENS-2X4-RED	Amber Green Red	LENS-2X4-BLU LENS-2X4-FR LENS-2X4-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X04-BBR 5000-X08-BZ 5000-X08-BK 5000-X08-BBR 5000-X12-BZ 5000-X12-BK 5000-X12-BBR	4 in 4 in 8 in 8 in 8 in 12 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X18-BBR 5000-X24-BZ 5000-X24-BK 5000-X24-BBR	18 in 18 in 18 in 24 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

#### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max* 



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122

9600-TRN-SS

600W Max

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 17 2022